



Home > Products > ProX Stands > Lighting Truss & Crankstands > 18 Ft Lighting Heavy-Duty Crank Truss Stand 500 Lb. Capacity with Outriggers Center Load 18' Includes T-Adapter Truss Mount

SKU: XT-CRANK18FT-500

Permalink: <http://www.proxdir.com>[Search on Google](#)

18 Ft Lighting Heavy-Duty Crank Truss Stand 500 Lb. Capacity with Outriggers Center Load 18' Includes T-Adapter Truss Mount

[Find A Dealer](#)

Product Images

[Download Product Images](#)

Our Products And You

[Submit your story](#)

18 Ft Lighting Heavy-Duty Crank Truss Stand 500 Lb. Capacity with Outriggers Center Load 18' Includes T-Adapter Truss Mount

Description

The **ProX XT-CRANK18FT-500 Heavy Duty Crank Stands** are an integral part of the Truss SQ System for temporarily mounting lights for small to medium-sized DJ lighting at any event. It has Integrated casters, independently adjustable leg braces, and nylon guided leg sliders, which can all be used in conjunction with another same-rated stand, & trusses and T-Adapters. Each is made with Heavy Duty All-metal components; Sturdy, steel/aluminum construction. Eliminate direct lifting and lowering of heavy loads with the ProX Truss Heavy Duty Crank Stand.

The ProX XT-CRANK18FT-500 is designed to support truss pieces, constructions, speakers, or other gear. This stand rises to a maximum height of 18', weighs 229 lb, and can support up to 500 lbs.

It folds easily to a portable size for transport. It's equipped with a smooth, heavy-duty cranking mechanism. Perfect for a live band and mobile DJ applications, eliminate direct lifting and lowering of heavy loads.

This stand, in conjunction with another XT-Crank18FT-500 stand & any length truss with T-Adapters XT-TADAPTER-500 allows you to mount and raise your lights to a maximum of 18 Ft. This combined system will support a maximum weight of 1000 lbs.

SAFETY INSTRUCTIONS

To avoid problems a competent person should inspect all rigging hardware, stands and equipment before each use and periodically do a major inspection for signs of wear, abuse and general adequacy, as well as perform any manufacturer recommended preventive maintenance on schedule. Observe all warnings and usage instructions in the full manual. Use at your own risk.

Features

- **Max Vert Load: 500 lbs.**
- **Base Diameter: 83.85" / 7FT**
- **Weight: 230 lbs.**
- **Min Height: 74"**
- **Base Closed: 24" x 19"**

Basic Usage:

1. Ensure that the stand is positioned on hard stable surface, in suitable location, on firm ground and clear of overhead obstacles.

2. Stabilize legs before lifting the tower or any load.
3. When outdoors, secure the tower with braces or cables, in case of wind.
4. Check the cable, it should not show damaged or flattened areas nor broken strands.

Using the Winch:

1. For Lifting the tower, turn the winch handle clockwise.
2. For lowering the tower, turn the winch handle counter-clockwise.

Safety Notes:

1. Loading on truss and stands should comply with rated weights.
2. Lock all the safety mechanisms (safety pins, knobs)
3. Loads must be centered & balanced on each lifting unit.
4. Safety chains must be installed on each item attached to unit.
5. Leave a safety perimeter with a radius 5ft greater than the maximum height of the stands during lifting and lowering of loads.
6. During transport, close all the sections and lock the lifting carriage.
7. Do not attempt to move the stand when loaded or in extended position.

Service Notes:

1. Servicing and repairs must be made by qualified persons.
2. Cable, pulleys and telescopic masts must be inspected before each use. Any damaged cable must be replaced immediately.
3. Annual inspection by an authorized technician is suggested.

Exterior Dimensions & Weight

76.00"H x 20.00"W x 24.00"L - Weight: 240.00 lbs

Suggested Shipping Method: LTL

Skid 1 pc 48x40x82" 335 LBS

Skid 2 pcs 48x40x82" 620 LBS

Skid 4 pcs: 48x40x82" 1190 LBS

UPC

741459147501

Our Products and You

Submit your
story

Commonly Asked Questions

+ Where can I buy one?

[submit a question](#)

Customer Testimonials

What did you think

Related Products



T-Adapter Support Bar for XT-CRANK18FT-500 Crank Stand System fits Stands 2 in. Diameter

SKU: XT-TADAPTER-500



14 Ft Heavy-duty Lighting Crank Stand for Lifting Truss Line Array Speakers 220 lbs Capacity

SKU: XT-CRANK14FT-220



XT-CRANK22FT-400 Heavy Duty 22 Ft. High Truss Crank Up Lighting Stand 400 Lbs. Capacity Includes T-Adapter Truss Mount

SKU: XT-CRANK22FT-400



9.84 Ft - 3.00 M F34 Square Truss Segment | 2 mm Wall

SKU: XT-SQ984



6 Way Square Truss Junction Block - Includes 2 Way 8 Half Conical Couplers

SKU: XT-JB6W-2W
